

What You Will Need:

Stain & Scale
 Natural & Clear
 Sodium Dichlor (Chlorine)

Test Strips
 pH/Alk Up
 pH/Alk Down

Activator (Weekly Shock)

Start Up (please make sure all pump unions are tight)

1. Set up your water maintenance

- a. All water comes with certain minerals and impurities. These chemicals help get your water clear and ready to use.
 - i. Add 3 oz of Stain and Scale when there is 4" or more of water in the bottom of the Spa
 - ii. Add 1/2 oz of Natural and Clear when there is 4" or more of water in the bottom of the Spa
- b. Fill Spa to half way mark of the skimmer
- c. Turn on Spa and wait until water is above 80 degrees

2. Balance your water.....

- a. pH and Alkalinity measure the acidity of your water. Step 2 helps you balance your water to prevent skin irritation and corrosion of spa parts.
 - i. Test pH with the test strips provided in your starter kit
 1. pH should measure between 7.2 - 7.8
 2. Alkalinity should measure between 80 - 120
 - ii. If adjustment is needed add 1 oz of Up or Down
 - iii. Check pH and Alkalinity after 15 minutes and adjust as necessary

3. Sanitize your water.....

- a. Sanitization keeps your water free of harmful bacteria, viruses and other organic matter that can cause your water to be cloudy.
 - i. Shock Spa with 1/2 oz of Chlorine

Weekly Maintenance

1. Water Maintenance

1. Add 1 oz of Stain and Scale to sequester metals and impurities
2. Add 1/2 oz of Natural and Clear to remove oils

2. Balance your water.....

1. Check pH and Alkalinity and adjust as necessary

3. Sanitize your water.....

1. Shock Spa with 2 oz of Activator
2. Check chlorine level twice a week to insure 1 - 3 ppm** of Chlorine. Adjust if necessary.
 - a. If low add 1/2 oz of Sodium Dichlor

Monthly Maintenance

Do your normal weekly maintenance but add Step 4.

4. Clean your spa

1. Wipe off your acrylic shell - clean off dust, water spots, chemical stains etc.
2. Clean and condition your cover - Remove dust, pollen, dirt or snow - condition it to protect it from the sun and cold
3. Clean your filters - Soak in cleaning solution, Rinse and dry. (You may have to do this every other week if you use your spa a lot.)
4. Check water in Spa Fill Spa to half way mark of skimmer

**NOTE: If you are using ThermoOzone, you may try to reduce your sanitizer level to a once to twice a week application and maintain a .5 ppm Chlorine level. (please read the ThermoOzone notes on the back of this page for more detail)